UNCLASSIFIED

AD NUMBER

NEW LIMITATION CHANGE

TO

Approved for public release, distribution unlimited

AD482328

FROM

Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; Mar 1966. Other requests shall be referred to Army Electronics Command, Atmospheric Sciences Lab, White Sands Missile Range, NM 88002-5501.

AUTHORITY

US Army Electronics Command ltr dtd 15 Sep 1971

482328

BOTHE COPY

ECOM-5039. March 1966

AD

OZONE MEASUREMENTS WITH ROCKET-BORNE OZONESONDES

By
JAGIR S. RANDHAWA



ATMOSPHERIC SCIENCES LABORATORY

WHITE SANDS MISSILE RANGE, NEW MEXICO

Best Available Copy





LIMITED STATES ARMY ELECTRONICS COMMAND

DDC AVAILABILITY

Qualified requesters may obtain copies of this report from DDC.

DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return it to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

OZONE MEASUREMENTS WITH ROCKET-BORNE OZONESONDES.

JAGIR S. RANDHAWA .

E Sin	tr .
	MAILE SISING []
	a 0
7 77	w1473
ON FRENCH	DOMESTIC COST
MOT.	MAIL ME & SVEIN

_	
11	
(/6/	DA PROMET -1L013001A91A

	(1	9)
(18)	ECOM /	5039

(13) Kp.

ATMOSPHERIC SCIENCES LABORATORY WHITE SANDS MISSILE RANSE, NEW MEXICO

1473 Jane

, /

ABSTRACT

A rocket-borne ozonesonde has been developed which utilizes the chemilum-inescent principle for the measurement of the ozone concentration in the atmosphere. This has been fired with the ARCAS rocket at White Sands Missile Range, New Mexico. The instrument, as it descends with the parachute, measures the ozone concentration. In addition to the main peak ozone concentration generally found near 22 km, a secondary peak has been observed close to 40 kilometers. A gross detailed structure of ozone distribution in the upper stratosphere has been measured which could not be obtained by the Umkehr method.

ACKNOWLEDGEMENT

I am grateful to Dr. V. H. Regener of the University of New Mexico at Albuquerque for suggesting the sampling procedure and also for supplying the chemiluminescent discs for the instruments.

CONTENTS

																										Page
ABSTRACT																				٠						444
INTRODUCTION																			_	•	•	•	•	•	•	,
INSTRUMENT .												_	_				·	•	Ĭ	•	•	•	•	•	•	
RESULTS								Ī		-	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	1
CONCLUSTONS	-		Ī	Ĭ	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•	6
CONCLUSIONS	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	6
REFERENCES .	-	•	•	•		•								_	_											۵

INTRODUCTION

In recent years knowledge of the vertical distribution of atmospheric ozone has been considerably increased, especially from data obtained by balloon-borne ozonesondes. The chemiluminescent-type ozonesonde developed by Regener (1960, 1964) and the bubbler-type electrochemical ozonesonde developed by Brewer and Milford (1960) are being used extensively for detailed measurements of the vertical ozone distribution. These balloon-borne sondes do not reach the top of the ozone layer, and the ozone concentration in the upper layers is evaluated by the Umkehr method. The need for an ozonesonde capable of measuring the complete ozone distribution in the atmosphere is an obvious one. The Regener chemiluminescent ozonesonde being a dry chemical instrument is quite suitable for adaptation to use in a small rocket.

A rocket-borne ozonesonde was developed for use with the ARCAS rocket system, and test firings have been conducted at White Sands Missile Range (WSMR), New Mexico. These sondes reached well above the stratopause and measured the ozone concentration while descending on a 15-foot diameter parachute. The circuitry of the photomultiplier tube has not been changed from Regener's original balloon-borne ozonesonde, and the Delta telemetry system (Clark and McCoy, 1965) operating at 1680 megacycles and using the AN/GMD-1 ground station has been adapted to recover the data.

INSTRUMENT

The rocket-borne ozonesonde (Figure 1) consists of three main parts: power supply, photomultiplier tube and sampling chamber, and telemetry circuit. The sampling chamber (Figure 2) consists of two concentric cylinders each having four windows of equal dimensions. The inner walls of the sampling chamber were painted with the chemiluminescent material. A photographic shutter is mounted at the bottom of the inner cylinder and a chemiluminescent disc is placed on the top, facing the shutter. The photomultiplier tube and associated circuitry are potted in a black silicone rubber and mounted below the sampling chamber. A rotary solenoid, mounted close to the telemetry circuit, controls the movement of the outer cylinder. When the outer cylinder of the sampling chamber is rotated to close the windows of the inner cylinder, the photographic shutter opens simultaneously, thus allowing the photomultiplier tube to see the chemiluminescent disc. A separate battery power (18 volts) required to actuate the solenoid is potted next to the photomultiplier tube.

A sequence timer in the ozonesonde actuates the rotary solenoid which in turn rotates the outer cylinder to take an ozone sample. The photon yield from the chemiluminescent disc is monitored by the photomultiplier tube, and the output is connected to the transmitter which operates at a carrier frequency of 1680 megacycles. In addition, an ozone zero signal and a temperature signal are briefly transmitted in a sequence. A 10-mil-diameter bead thermistor (Figure 1) with a thin-film mount is used to record atmospheric temperature.

The instrument is calibrated before launch by the use of an ozone generator (Regener, 1964) for absolute measurement of ozone concentration in the atmosphere. Ozonized air of a known concentration is injected into the sampling chamber (which is enclosed in a jacket) and sensitivity is set in the proper range.




Figure 1. Rocket-borne ozonesonde.




Figure 2. Sampling chamber.




Figure 3. Ozone distribution with height.




Figure 4. Ozone distribution with height.

The ozonesonde is deployed from the ARCAS rocket at apogee (approximately 130 seconds after launch), the nose cone falls clear, and the instrument returns to earth on a 15-foot-diameter radar-reflective parachute. The radar track of the parachute yields wind data while the temperature and ozone data are received by the Rawin set AN/GMD-1 receiver. As the payload descends on the parachute, ozone concentration is sampled every twenty seconds. The instrument package weighs 3½ kg and the fall rate is approximately 120 meters per second at 50 km altitude and 30 meters per second at 30 km altitude.

RESULTS

The rocket ozonesonde firings completed thus far were scheduled during dark nights to minimize contamination of the photomultiplier output by stray light. The data reduced from October and November firings are presented in Figures 3 and 4. These data show considerable variations in the ozone concentration in the stratosphere which could be attributed to atmospheric conditions. In addition to the peak ozone concentration generally found near 22 km, a secondary peak of smaller amplitude is observed close to 40 kilometers. The higher altitude peak may be considered to be a Chapman peak and the lower as a storage peak. The loss of ozone in between the two peaks could be due to the stratospheric aerosols as suggested by Kroening (1965). Another interesting point shown in the data is the decrease from 22 km to less than 20 km in the height of the main ozone peak during a month's time.

Figure 5 shows the temperature profile as obtained with the bead thermistor on October 25, 1965, 2100 MST. The bead thermistor was not mounted on the November firing so that the frequency of ozone observations could be increased.

The rocket ozonesonde has sufficient resolution to measure the detailed structure of the ozone distribution in the upper stratosphere. The data obtained do not agree with the profiles evaluated by the Umkehr method in detail; however, the total amount of ozone found by integrating on these days agrees very well with that obtained by the Dobson spectrophotometer at the corresponding latitude and time of the year. The heights of the main ozone peaks on these days also agree favorably with those obtained by the balloonsondes.

CONCLUSIONS

The chemiluminescent measurement technique has permitted the monitoring of ozone concentration in higher altitudes of the atmosphere and has given the detailed structure of the ozone distribution in the upper stratosphere. Sufficient observations have not been made to draw detailed conclusions; however, in all the firings, a secondary peak in ozone concentration has been observed around 40 kilometers.




Figure 5. Temperature over White Sands Missile Range.

REFERENCES

- Brewer, A. W., and J. R. Milford, 1900: The Oxford-Kew Ozonesonde, <u>Proc. Roy.</u> Soc. London, A. 256, 470.
- Clark, G. Q., and J. G. McCoy, 1965: Measurements of Stratospheric Temperature, J. Appl. Meteorol., 4, 365-370.
- Kroening, J. 1., 1965: Stratosphere and Troposphere: Transport of Material Between Them. <u>Science</u>, 147, 862.
- Regener, V. H., 1960: On a Sensitive Method for the Recording of Atmospheric Ozone, <u>J. Geophys. Res.</u>, 65, 3975-3977.
- Regener, V. H., 1964: Measurement of Atmospheric Ozone with the Chemiluminescent Method, J. Geophys. Res., 69, 3795-3800.

ATMOSPHERIC SCIENCES RESEARCH PAPERS

- Webb, W.L., "Development of Droplet Size Distributions in the Atmosphere," June 1954.
- Hansen, F. V., and H. Rachele, "Wind Structure Analysis and Forecasting Methods for Rockets," June 1954.
- Webb, W. L., "Net Electrification of Water Droplets at the Earth's Surface," J. Meteorol., December 1954.
- Mitchell, R., "The Determination of Non-Ballistic Projectile Trajectories," March 1955.
- Webb, W. L., and A. McPike, "Sound Ranging Technique for Determining the Trajectory of Supersonic Missiles," #1, March 1955.
- Mitchell, R., and W. L. Webb, "Electromagnetic Radiation through the Atmosphere," #1, April 1955.
- Webb, W. L., A. McPike, and H. Thompson, "Sound Ranging Technique for Determining the Trajectory of Supersonic Missiles," #2, July 1955.
- Barichivich, A., "Meteorological Effects on the Refractive Index and Curvature of Microwaves in the Atmosphere," August 1955.
- Webb, W. L., A. McPike and H. Thompson, "Sound Ranging Technique for Determining the Trajectory of Supersonic Missiles," #3, September 1955.
- Mitchell, R., "Notes on the Theory of Longitudinal Wave Motion in the Atmosphere," February 1956.
- 11. Webb, W. L., "Particulate Counts in Natural Clouds," J. Meteorol., April 1956.
- 12. Webb, W. L., "Wind Effect on the Aerobee," #1, May 1956.
- 13. Rachele, H., and L. Anderson, "Wind Effect on the Aerobee," #2, August 1956.
- 14. Beyers, N., "Electromagnetic Radiation through the Atmosphere," #2, January 1957.
- 15. Hansen, F. V., "Wind Effect on the Aerobee," #3, January 1957.
- 16. Kerehner, J., and H. Bear, "Wind Effect on the Aerobee," #4, January 1957.
- Hoidale, G., "Electromagnetic Radiation through the Atmosphere," #3, February 1957.
- Querfeld, C. W., "The Index of Refraction of the Atmosphere for 2.2 Micron Radiation," March 1957.
- 19. White, Lloyd, "Wind Effect on the Aerobee," #5, March 1957.

- Kershner, J. G., "Development of a Method for Forecasting Component Ballistic Wind," August 1957.
- 21. Layton, Ivan, "Atmospheric Particle Size Distribution," December 1957.
- Rachele, Henry and W. H. Hatch, "Wind Effect on the Aerobee," #6, February 1958.
- Beyers, N. J., "Electromagnetic Radiation through the Atmosphere," #4, March 1958.
- Prosser, Shirley J., "Electromagnetic Radiation through the Atmosphere," #5, April 1958.
- Hoidale, G., "Electromagnetic Propagation through the Atmosphere," #6, February 1959.
- McLardie, M., R. Helvey, and L. Traylor, "Low-Level Wind Profile Prediction Techniques," #1, June 1959.
- 27. Lamberth, Roy, "Gustiness at White Sands Missile Range," #1, May 1959.
- Beyers, N. J., B. Hinds, and G. Hoidale, "Electromagnetic Propagation through the Atmosphere," #7, June 1959.
- Hainline, D. A., "Drag Cord-Aerovane Equation Analysis for Computer Application," August 1959.
- 30. Hoidale, G. B., "Slope-Valley Wind at WSMR," October 1959.
- 31. Webb, W. L., and K. R. Jenkins, "High Altitude Wind Measurements," J. Meteorol., 16, 5, October 1959.
- 32. White, Lloyd, "Wind Effect on the Aerobee," #9, October 1959.
- 33. Webb, W. L., J. W. Coffman, and G. Q. Clark, "A High Altitude Acoustic Sensing System," December 1959.
- 34. Webb, W. L., and K. R. Jenkins, "Application of Meteorological Rocket Systems," J. Geophys. Res., 64, 11, November 1959.
- 35. Duncan, Louis, "Wind Effect on the Aerobee," #10, February 1960.
- Helvey, R. A., "Low-Level Wind Profile Prediction Techniques," #2, February 1960.
- Webb, W. L., and K. R. Jenkins, "Rocket Sounding of High-Altitude Parameters," Proc. GM Rel. Symp., Dept. of Defense, February 1960.
- 38. Webb, W. L., and K. R. Jenkins. "Speed of Sound in the Stratosphere," June 1960.
- Webb, W. L., K. R. Jenkins, and G. Q. Clark, "Rocket Sounding of High Atmosphere Meteorological Parameters," IRE Trans. Mil. Elect., MIL-4, 2-3, April-July 1960.

- Helvey, R. A., "Low-Level Wind Profile Prediction Techniques," #3, September 1960.
- 41. Beyers, N. J., and O. W. Thiele, "Meteorological Wind Sensors," August 1960.
- Armijo, Larry, "Determination of Trajectories Using Range Data from Three Noncolinear Radar Stations," September 1960.
- Cames, Patey Sue, "Temperature Variations in the First 200 Feet of the Atmosphere in an Arid Region," July 1961.
- Springer, H. S., and R. O. Olsen, "Launch Noise Distribution of Nike-Zeus Missiles," July 1961.
- Thiele, O. W., "Density and Pressure Profiles Derived from Meteorological Rocket Measurements," September 1961.
- Diamond, M. and A. B. Gray, "Accuracy of Missile Sound Ranging," November 1961.
- Lamberth, R. L. and D. R. Veith, "Variability of Surface Wind in Short Distances," #1, October 1961.
- Swanson, R. N., "Low-Level Wind Measurements for Ballistic Missile Application," January 1962.
- Lamberth, R. L. and J. H. Grace, "Gustiness at White Sands Missile Range," #2, January 1962.
- Swanson, R. N. and M. M. Hoidale, "Low-Level Wind Profile Prediction Techniques," #4, January 1962.
- Rachele, Henry, "Surface Wind Model for Unguided Rockets Using Spectrum and Cross Sprectrum Techniques," January 1962.
- Rachele, Henry, "Sound Propagation through a Windy Atmosphere," #2, February 1962.
- Webb, W. L., and K. R. Jenkins, "Sonic Structure of the Mesosphere," J. Acous. Soc. Amer., 34, 2, February 1962.
- Tourin, M. H. and M. M. Hoidale, "Low-Level Turbulence Characteristics at White Sands Missile Range," April 1962.
- Miers, Bruce T., "Mesospheric Wind Reversal over White Sands Missile Range," March 1962.
- Fisher, E., R. Lee, and H. Rachele, "Meteorological Effects on an Acoustic Wave within a Sound Ranging Array," May 1962.
- 87. Walter, E. L., "Six Variable Ballistic Model for a Rocket," June 1962.
- Webb, W. L., "Detailed Acoustic Structure Above the Tropopause," J. Applied Meteorol., 1, 2, June 1962.

- Lamberth, Roy, "Wind Variability Estimates as a Function of Sampling Interval," July 1962.
- Rachele, Henry, "Surface Wind Sampling Periods for Unguided Rocket Impact Prediction," July 1962.
- 61. Traylor, Larry, "Coriolis Effects on the Aerobee-Hi Sounding Rocket," August 1962.
- 62. McCoy, J., and G. Q. Clark, "Meteorological Rocket Thermometry." August 1962.
- 63. Rachele, Henry, "Real-Time Prelaunch Impact Prediction System," August 1962.
- Beyers, Norman, and Norman Wagner, "Performance Characteristics of Meteorological Rocket Wind and Temperature Sensors," October 1962.
- 65. Colfman, J., and R. Price, "Some Errors Associated with Acoustical Wind Measurements through a Layer," October 1962.
- Armendariz, M., E. Fisher, and J. Serna, "Wind Shear in the Jet Stream at WS-MR," November 1962.
- Armendariz, M., F. Hansen, and S. Carnes, "Wind Variability and its Effect on Rocket Impact Prediction," January 1963.
- 68. Querfeld, C., and Wayne Yunker, "Pure Rotational Spectrum of Water Vapor, I: Table of Line Parameters," February 1963.
- 69. Webb, W. L., "Acoustic Component of Turbulence," J. Applied Meteorol., 2, 2, April 1963.
- 70. Beyers, N. and L. Engberg, "Seasonal Variability in the Upper Atmosphere," May
- 71. Lamberth, Roy and D. Veith, "Upper Wind Correlations in Southwestern United States," June 1963.
- 72. Sandlin, E., "An Analysis of Wind Shear Differences as Measured by AN/FPS-16 Radar and AN/GMD-1B Rawinsonde," August 1963.
- 73. Diamond, M. and R. P. Lee, "Statistical Data on Atmospheric Design Properties Above 30 km," August 1963.
- Thiele, O. W., "Mesospheric Density Variability Based on Recent Meteorological Rocket Measurements," J. Applied Meteorol., 2, 5, October 1963.
- Diamond, M., and O. Essenwanger, "Statistical Data on Atmospheric Design Properties to 30 km," Astro. Aero. Engr., December 1963.
- Hansen, F. V., "Turbulence Characteristics of the First 62 Meters of the Atmosphere," December 1963.
- Morris, J. E., and B. T. Miers, "Circulation Disturbances Between 25 and 70 kilometers Associated with the Sudden Warming of 1963," J. of Geophys. Res., January 1964.

- Thiele, O. W., "Some Observed Short Term and Diurnal Variations of Stratospheric Density Above 30 km," January 1964.
- Sandlin, R.E., Jr. and E. Armijo, "An Analysis of AN/FPS-16 Radar and AN GMD-1B Rawinsonde Data Differences," January 1964.
- 80. Miers, B. T., and N. J. Beyers, "Rocketsonde Wind and Temperature Measurements Between 30 and 70 km for Selected Stations," J. Applied Meteorol., February 1964.
- 81. Webb, W. L., "The Dynamic Stratosphere," Astronautics and Aerospace Engineering, March 1964.
- 82. Low, R. D. H., "Acoustic Measurements of Wind through a Layer," March 1964.
- 83. Diamond, M., "Cross Wind Effect on Sound Fropagation," J. Applied Meteorol., April 1964.
- 84. Lee, R. P., "Acoustic Ray Tracing," April 1984.
- Reynolds, R. D., "Investigation of the Effect of Lapse Rate on Balloon Ascent Rate," May 1964.
- Webb, W. L., "Scale of Stratospheric Detail Structure," Space Research V, May 1964.
- Barber, T. L., "Proposed X-Ray-Infrared Method for Identification of Atmospheric Mineral Dust," June 1964.
- 88. Horn, J. D., and E. J. Trawle, "Orographic Effects on Wind Variability," July 1964.
- 89. Hoidale, G., C. Querfeld, T. Hall, and R. Mireles, "Spectral Transmissivity of the Earth's Atmosphere in the 250 to 500 Wave Number Interval," #1, September 1964.
- Duncan, L. D., R. Ensey, and B. Engebos, "Athena Launch Angle Determination," September 1964.
- Duncan, L. D., and R. Ensey, "Six-Degree-of-Freedom Digital Simulation Model for Unguided, Fin-Stabilized Rockets," November 1964.
- 92. Hoidale, G., C. Querfeld, T. Hall, and R. Mireles, "Spectral Transmissivity of the Earth's Atmosphere in the 250 to 500 Wave Number Interval," #2, November 1964.
- 93. Webb, W. L., "Stratospheric Solar Response," J. Atmos. Sci., November 1964.
- McCoy, J. and G. Clark, "Rocketsonde Measurement of Stratospheric Temperature," December 1964.
- Farone, W. A., "Electromagnetic Scattering from Radially Inhomogeneous Spheres as Applied to the Problem of Clear Atmosphere Radar Echoes," December 1964.

- 96. Farone, W. A., "The Effect of the Solid Angle of Illumination or Observation on the Color Spectra of "White Light" Scattered by Cylinders," January 1965.
- 97. Williamson, L. E., "Seasonel and Regional Characteristics of Acoustic Atmospheres,"

 J. Geophys. Res., January 1965.
- 98. Armendariz, M., "Ballistic Wind Variability at Green River, Utah," January 1965.
- Low, R. D. H., "Sound Speed Variability Due to Atmospheric Composition," January 1965.
- 100. Querfeld, C. W., "Mie Atmospheric Optics," J. Opt. Soc. Amer., January 1965.
- Coffman, J., "A Measurement of the Effect of Atmospheric Turbulence on the Coherent Properties of a Sound Wave," January 1965.
- Rachele, H., and D. Veith. "Surface Wind Sampling for Unguided Rocket Impact Prediction," January 1965.
- Ballard, H., and M. Izquierdo, "Reduction of Microphone Wind Noise by the Generation of a Proper Turbulent Flow," February 1965.
- Mireles, R., "An Algorithm for Computing Half Widths of Overlapping Lines on Experimental Spectra," February 1965.
- Richart, H., "Inaccuracies of the Single-Theodolite Wir leasuring System in Ballistic Application," February 196!
- 106. D'Arcy, M., "Theoretical and Practical Study of Aerobee-150 Ballistics," March 1965.
- McCoy, J., "Improved Method for the Reduction of Rocketsonde Temperature Data," March 1965.
- Mireles, R., "Uniqueness Theorem in Inverse Electromagnetic Cylindrical Scattering," April 1965.
- Coffman, J., "The Focusing of Sound Propagating Vertically in a Horizontally Stratified Medium," April 1965.
- Farone, W. A., and C. Querfeld, "Electromagnetic Scattering from an Infinite Circular Cylinder at Oblique Incidence," April 1965.
- 111. Rachele, H., "Sound Propagation through a Windy Atmosphere," April 1965.
- 112. Miera, B., "Upper Stratospheric Circulation over Ascension Island," April 1965.
- Rider, L., and M. Armendariz, "A Comparison of Pibal and Tower Wind Measurements," April 1965.
- 114. Hoidale, G. B., "Meteorological Conditions Allowing a Rare Observation of 24 Micron Solar Radiation Near Sea Level," Meteorol. Magazine, May 1965.
- 115. Beyers, N. J., and B. T. Miers, "Diurnal Temperature Change in the Atmosphere Between 30 and 60 km over White Sands Missile Range," J. Atmos. Sci., May 1965.

- 116. Querfeld, C., and W. A. Farone, "Tables of the Mie Forward Lobe," May 1965.
- Farone, W. A., "Generalization of Rayleigh-Gans Scattering from Radially Inhomogeneous Spheres," J. Opt. Soc. Amer., June 1965.
- Diamond, M., "Note on Mesospheric Winds Above White Sands Missile Range," J. Applied Meteorol., June 1965.
- 119. Clark, G. Q., and J. G. McCoy, "Measurement of Stratospheric Temperature," J. Applied Mcteorol., June 1965.
- Hall, T., G. Hoidale, R. Mireles, and C. Querfeld, "Spectral Transmissivity of the Earth's Atmosphere in the 250 to 500 Wave Number Interval," #3, July 1965.
- 121. McCoy, J., and C. Tate, "The Delta-T Meteorolobical Rocket Payload," June 1965.
- 122. Horn, J. D., "Obstacle Influence in a Wind Tunnel," July 1965.
- 123. McCoy, J., "An AC Probe for the Measurement of Electron Density and Collision Frequency in the Lower Ionosphere," July 1965.
- Serna, J., "An Acoustic Ray Tracing Method for Digital Computation," September 1965.
- 125. Webb, W. L., "Morphology of Noctilucent Clouds," J. Geophys. Res., 70, 18, 4463-4475, September 1965.
- Kays, M., and R. A. Craig, "On the Order of Magnitude of Large-Scale Vertical Motions in the Upper Stratosphare," J. Geophys. Res., 70, 18, 4453-4462, September 1965.
- Lamberth, R. L., R. Reynolds, and Morton Wurtele, "The Mountain Lee Wave at White Sands Missile Range," Bull. Amer. Meteorol. Soc., 46, 10, October 1965.
- 128. Reynolds, R. and R. L. Lamberth, "Ambient Temperature Measurements from Radiosondes Flown on Constant-Level Balloons," October 1965.
- 129. McCluney, E., "Theoretical Trajectory Performance of the Five-Inch Gun Probe System," October 1965.
- Pena, R. and M. Diamond, "Atmospheric Sound Propagation near the Earth's Surface," October 1965.
- Mason, J. B., "A Study of the Feasibility of Using Radar Chaff For Stratospheric Temperature Measurements," November 1965.
- 132. Diamono, M., and R. P. Lee, "Long-Range Atmospheric Sound Propagation," J. Geophys. Res., 70, 22, November 1965.
- Lamberth, R. L., "On the Measurement of Dust Devil Parameters," November 1965.
- 134. Hansen, F. V., and P. S. Hansen, "Formation of an Internal Boundary over Heterogeneous Terrain," November 1965.

- 135. Webb, W. L., "Mechanics of Stratospheric Seasonal Reversals," November 1965.
- U. S. Army Electronics R & D Activity, "U. S. Army Participation in the Meteorological Rocket Network," January 1966.
- 137. Rider, L. J., and M. Armendariz, "Low-Level Jet Winds at Green River, Utah," February 1966.
- 138. Webb, W. L., "Diurnal Variations in the Stratospheric Circulation," February 1966.
- 139. Beyers, N. J., B. T. Miers, and R. J. Reed, "Diurnal Tidal Motions near the Stratopause During 48 Hours at WSMR," February 1966.
- 140. Webb, W. I., "The Stratospheric Tidal Jet," February 1966.
- 141. Hall, J. T., "Focal Properties of a Plane Grating in a Convergent Beam," February 1966.
- Duncan, L. D., and Henry Rachele, "Real-Time Meteorological System for Firing of Unguided Rockers," February 1966.
- Duncan, L. D., "Coordinate Transformations in Trajectory Simulations," February 1966.
- Williamson, L. E., "Gun-Launched Vertical Probes at White Sands Missile Range," February 1966.
- 145. Randhawa, J. S., "Ozone Measurements with Rocket-Borne Ozonesondes," March 1966.

INCLASSIFIED Security Classification DOCUMENT CONTROL DATA - RAD ES. REPORT SECURITY & LASSIFICATION Unclassified U.S. Army Electronics Command Fort Monmouth, New Jersey Ozone Measurements with Rocket-Borne Ozones ondes 4 DESCRIPTIVE HOTES (Type of separt and inchistre delea) \$ AUTHORIS (Last name, Emt name, billiot) Randhawa, Jagir S. -16 March 1966 3. CONTRACT OR BRANT NO. SIMP TOR'S REPORT HUMBS & PROJECT NO. **ECOM - 5039** DA Project 11013001A91A Sh. O THER REPORT HE(E) (Aur offer mentere fint mer be designed TO AVAILABILITY/LIMITATION HOTITES Qualified requesters may obtain copies of this report from DDC. II. SUPPL EMENTARY HOTES 12. SPONSORING MILITARY ACTIVITY U.S. Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico 15 STRACT A rocket-borne ozonesonde has been developed which utilizes the chemilumines cent principle for the messurement of the ozone concentration in the atmosphere. This has been fixed with the ARCAS rocket at White Sands Missile Range, New Mexico. The instrument, as it descends with the parachute, measures the ozone concentration. In addition to the main peak ozone concentration generally found near 22 km, a secondary peak has been observed close to 40 kilometors. A gross detailed structure of ezone distribution in the upper stratosphere has been nessured which could not be obtained by the Unitehr method.

INCLASSIFIED

Security Classification

DD . 1473

T14.		LIN	K A	LIN	K B	LINK C		
	KEY WORDS	ROLE	WT	ROLE	WT	ROLE	WT	
1. 2. 3. 4. 5.	Ozonosphere Ozonesonde Chemiluminescent Chapman Peak Storage Peak	ROLE		ROLE		ROCE		
	NAME (OT) AN	<u> </u>	L					

INSTRUCTIONS

- 1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.
- 24. REPORT SECURITY CLASSIFICATION: Enter the over all security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. GROUP: Automatic downgrading is specified in DoD Directive 5200, 10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as author-
- 3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in paremhesis immediately following the title.
- 4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final.
 Give the inclusive dates when a specific reporting period is covered.
- 5. AUTHOR(S): Enter the name(a) of author(a) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
- 6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 76. NUMBER OF REFERENCES: Enter the total number of references cited in the report.
- 8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the repor! was written.
- 8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military cepartment identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. OTHER REPORT NUMBER(8): If the report has been anaigned any other report numbers (either by the originator or by the aponsor), also enter this number(s).

- 10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:
 - (1) "Qualified requesters may obtain copies of this report from DDC."
 - (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
 - (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through
 - (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
 - (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indi-cate this fact and enter the price, if known.

- 11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.
- 12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.
- 13. ABSTRACT: Enter an abstract giving a brief and factual aummary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shell be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (75), (5), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phranes that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Idenflers, such as equipment model designation, trade name, mili-tary project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is

UNCLASSIFIED

[This page is intentionally left blank.]

UNCLASSIFIED